

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
28 April 2005 (28.04.2005)

PCT

(10) International Publication Number
WO 2005/038968 A2

(51) International Patent Classification⁷: H01M 8/00

(21) International Application Number:
PCT/NL2004/000739

(22) International Filing Date: 19 October 2004 (19.10.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
1024573 20 October 2003 (20.10.2003) NL

GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(71) Applicant and

(72) Inventor: JANSSEN, Catharina, Philippina [NL/NL];
Rijksweg 35 B, NL-6584 AA Molenhoek (NL).


Published:

— without international search report and to be republished upon receipt of that report

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: SUSPENSION FOR THE GENERATION OF A CURRENT OF ELECTRONS AND THE USE AND THE PREPARATION THEREOF



(57) Abstract: The present invention relates to a suspension that can be used to generate a current of electrons, which suspension comprises a polypeptide, wherein the polypeptide is entrapped in a hollow particle. It furthermore relates to the use of the suspension described above for the production of a battery. More specifically the present invention relates to the use of the suspension described above for the production of a nano-battery for the use in combination with a microchip. The present invention also relates to a battery using the suspension described above. In another aspect the present invention relates to a fuel cell, comprising: an anode compartment including an anode; a cathode compartment including a cathode; and disposed within said anode compartment, within said cathode compartment, or between said anode compartment and said cathode compartment, the suspension described above. In addition the present invention relates to a device for detection of a solute using the suspension described above, and more specifically to a device for the detection of glucose. In still another aspect the present invention relates to a method for producing electrical power, comprising the use of the suspension described above. Furthermore the invention relates to a method for preparing the suspension described above, comprising the steps of (a) making an aqueous solution of bis(2,2'-bipyridine)ruthenium(II)bis(pyrazolyl); (b) injecting a solution containing polystyrene-*b*-poly(L-isocyanoalanine(2-thiophen-3-yl-ethyl)amide) in THF into the solution made in step (a) preferably also comprising (c) placing the dispersion made in step (b) at 60 °C; (d) cooling the dispersion to room temperature, and (e) filter the dispersion of step (d) using a filter with a cutoff of 100 kDa.